

SurePassExams



- ✓ Online Tool, Convenient, easy to study.
- ✓ Instant Online Access
- ✓ Supports All Web Browsers
- ✓ Practice Online Anytime
- ✓ Test History and Performance Review
- ✓ Supports Windows / Mac / Android / iOS, etc.



- ✓ Installable Software Application
- ✓ Simulates Real Exam Environment
- ✓ Builds Exam Confidence
- ✓ Supports MS Operating System
- ✓ Two Modes For Practice
- ✓ Practice Offline Anytime



- ✓ Printable PDF Format
- ✓ Prepared by IT Experts
- ✓ Instant Access to Download
- ✓ Study Anywhere, Anytime
- ✓ 365 Days Free Updates
- ✓ Free PDF Demo Available



Security & Privacy

We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.



365 Days Free Updates

Free update is available within 365 days after your purchase. After 365 days, you will get 50% discounts for updating.



Money Back Guarantee

Full refund if you fail the corresponding exam in 90 days after purchasing. And Free get any another product.



Instant Download

After Payment, our system will send you the products you purchase in mailbox in a minute after payment. If not received within 2 hours, please contact us.

<http://www.surepassexams.com/>

Legal & authoritative company offering the highest pass-rate Exam Torrent materials and helping use pass for sure.

Exam : **1z1-400**

Title : Oracle Communications
Session Border Controller
Implementation Essentials

Vendor : Oracle

Version : DEMO

NO.1 Which two alarm reporting mechanisms are available to provide fault information for your Session Border Controller in a VOIP network?

- A. The Acme Packet Net-Net 4000 Element Management System (EMS)
- B. CMIP fault/response messages
- C. Rear craft interface display
- D. SNMP traps
- E. Via the show system-alarms ACLI command

Answer: C,E

NO.2 In a peering environment based on SIP-NAT Bridge, which two elements must be configured to accommodate signaling and media?

- A. Physical Interface
- B. Network Interface
- C. SIP Manipulation Rule
- D. RTP Table
- E. Local Policy

Answer: B,C

NO.3 On a Net-Net 4500, a hardware-based timer will reset the system in the event of a catastrophic software or operating system failure.

This hardware timer is reset (preventing it from triggering) by the_____.

- A. Acme Control Protocol Daemon
- B. Border Element Redundancy Protocol Daemon (BERPD)
- C. Console-timeout/telnet-timeout configuration in system-config
- D. System clock
- E. Watchdog process

Answer: E

NO.4 Which statements are TRUE about a Net-Net 4500 SIP interface?

- A. The SIP interface provides G.711 to G.729 transcoding functions ONLY when SIP is the signaling protocol.
- B. The SIP interface listens for SIP signaling on one or more configured IP address/port/transport combinations.
- C. You can only configure a single SIP port per realm.
- D. The SIP interface provides a service pipe to sipd, such that incoming signaling messages are presented to the SIP protocol daemon for processing.
- E. The SIP interface modifies headers, such as the TO and FROM, to provide topology hiding.

Answer: B

NO.5 Which statement about the Net-Net 4500 is FALSE?

- A. The Net-Net 4500 can perform interworking between SIP REGISTER messages and H.323 RROs (Registration Request).
- B. Different SIP Response Code mappings can be configured for each Soft-switch to which the Net-

Net 4500 signals.

C. MGCP to SIP interworking function (IWF) is not supported.

D. The Net-Net 4500 media directing and control hides network topology at the forwarding level, while session routing and signaling hide it at the signaling level.

E. The Net-Net 4500 is the source and destination for all signaling messages and media streams coming into and leaving the provider's network.

Answer: B

NO.6 _____ is the percentage of a Session Border Controller's peer advertisement time for the other peer in the high availability (HA) pair to wait before considering the peer out of service.

A. 2

B. Percent-drift

C. 3.1

D. Standard-deviation-score

E. State-field

Answer: B

NO.7 Which H.323 signaling technology is used between endpoints to establish a connection?

A. H.225.0 Q.931

B. H.225.0 RAS

C. H.245

D. H.261

E. H.263

Answer: C